

CERTIFICATE

No. U6 089086 0394 Rev. 00

Holder of Certificate: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:




Product: **Power supplies**
(Dimmable Constant Current LED Driver)

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142235022301

Date, 2023-08-18



(Taylor Yao)

CERTIFICATE

No. U6 089086 0394 Rev. 00

Model(s):

BK-DAL030-B0800Ad, BK-DAL030-B0800AD,
BK-DBL030-A0800ADF, BK-DBL030-A0800ADP,
BK-DAL030-BXXXXADR, BK-DBL030-AXXXADN,
BK-DBL030-AXXXADPR, BK-DAL040-B1050Ad,
BK-DAL040-B1050AD, BK-DBL040-A1050ADF,
BK-DBL040-A1050ADP, BK-DAL040-BXXXXADR,
BK-DBL040-AXXXADN, BK-DBL040-AXXXADPR,
BK-DAL050-B1300Ad, BK-DAL050-B1300AD,
BK-DBL050-A1300ADF, BK-DBL050-A1300ADP,
BK-DAL050-BXXXXADR, BK-DBL050-AXXXADN,
BK-DBL050-AXXXADPR, BK-DAL060-B1650Ad,
BK-DAL060-B1650AD, BK-DBL060-A1650ADF,
BK-DBL060-A1650ADP, BK-DAL060-BXXXXADR,
BK-DBL060-AXXXADN, BK-DBL060-AXXXADPR,
BK-DAL080-B2000Ad, BK-DAL080-B2000AD,
BK-DBL080-A2000ADF, BK-DBL080-A2000ADP,
BK-DAL080-BXXXXADR, BK-DBL080-AXXXADN,
BK-DBL080-AXXXADPR

(XXXX=0100-2000 indicates rated output current (I_{rated})
100-2000mA, in steps of 1mA)

Brand Name:

BOKE



Parameters:

Rated Input Voltage: 200-240V AC/DC
Rated Frequency: 0/50/60Hz
Rated Input Current: See below table for details
Rated Output: See below table for details
Protection against Electric Shock: Class I (with endcap); SELV
Degree of Protection: IP20 (with endcap)
Method of Installation: Independent (with endcap);
Built-in (without endcap)
Type of Output: Constant current type
ta: 60°C
tc: 90°C

**Tested
according to:**

EN 61347-1:2015/A1:2021
EN 61347-2-13:2014/A1:2017
EN IEC 62384:2020

**Production
Facility(ies):**

089086

CERTIFICATE

No. U6 089086 0394 Rev. 00

Model	Rated Input Current (A) Max.	Output Voltage (VDC)	I _{rated} (mA)	P _{rated} (W) Max.	U _{out} (VDC)
BK-DAL030-B0800Ad, BK-DAL030-B0800AD, BK-DBL030-A0800ADF, BK-DBL030-A0800ADP	0.19	6-42	275	11.55	50
		6-42	300	12.6	
		6-42	325	13.65	
		6-42	350	14.7	
		6-42	375	15.75	
		6-42	400	16.8	
		6-42	425	17.85	
		6-42	450	18.9	
		6-42	475	19.95	
		6-42	500	21.0	
		6-42	550	23.1	
		6-42	600	25.2	
		6-42	650	27.3	
		6-40	750	30.0	
6-38	800	30.4			
BK-DAL030-BXXXXADR, BK-DBL030-AXXXXADN, BK-DBL030-AXXXXADPR	0.19	6-42	100-800	30.4	50
BK-DAL040-B1050Ad, BK-DAL040-B1050AD, BK-DBL040-A1050ADF, BK-DBL040-A1050ADP	0.24	6-42	400	16.8	50
		6-42	425	17.85	
		6-42	450	18.9	
		6-42	475	19.95	
		6-42	500	21.0	
		6-42	550	23.1	
		6-42	600	25.2	
		6-42	650	27.3	
		6-42	700	29.4	
		6-42	750	31.5	
		6-42	800	33.6	
		6-42	850	35.7	
		6-42	900	37.8	
		6-42	950	39.9	
6-40	1000	40.0			
6-38	1050	39.9			
BK-DAL040-BXXXXADR, BK-DBL040-AXXXXADN, BK-DBL040-AXXXXADPR	0.24	6-42	200-1050	40.0	50
BK-DAL050-B1300Ad, BK-DAL050-B1300AD, BK-DBL050-A1300ADF, BK-DBL050-A1300ADP	0.29	6-42	550	23.1	50
		6-42	600	25.2	
		6-42	650	27.3	
		6-42	700	29.4	
		6-42	750	31.5	
		6-42	800	33.6	
		6-42	850	35.7	
		6-42	900	37.8	
		6-42	950	39.9	
		6-42	1000	42.0	
		6-42	1050	44.1	
		6-42	1100	46.2	
		6-42	1150	48.3	
		6-42	1200	50.4	
6-40	1250	50.0			
6-38	1300	49.4			

CERTIFICATE

No. U6 089086 0394 Rev. 00

BK-DAL050-BXXXXADR, BK-DBL050-AXXXXADN, BK-DBL050-AXXXXADPR	0.29	6-42	350-1300	50.4	50
BK-DAL060-B1650Ad, BK-DAL060-B1650AD, BK-DBL060-A1650ADF, BK-DBL060-A1650ADP	0.38	6-42	900	37.8	50
		6-42	950	39.9	
		6-42	1000	42.0	
		6-42	1050	44.1	
		6-42	1100	46.2	
		6-42	1150	48.3	
		6-42	1200	50.4	
		6-42	1250	52.5	
		6-42	1300	54.6	
		6-42	1350	56.7	
		6-42	1400	58.8	
		6-42	1450	60.9	
		6-40	1550	62.0	
		6-38	1600	60.8	
6-38	1650	62.7			
BK-DAL060-BXXXXADR, BK-DBL060-AXXXXADN, BK-DBL060-AXXXXADPR	0.38	6-42	700-1650	63.0	50
BK-DAL080-B2000Ad, BK-DAL080-B2000AD, BK-DBL080-A2000ADF, BK-DBL080-A2000ADP	0.47	6-42	1250	52.5	50
		6-42	1300	54.6	
		6-42	1350	56.7	
		6-42	1400	58.8	
		6-42	1450	60.9	
		6-42	1500	63.0	
		6-42	1550	65.1	
		6-42	1600	67.2	
		6-42	1650	69.3	
		6-42	1700	71.4	
		6-42	1750	73.5	
		6-42	1800	75.6	
		6-42	1850	77.7	
		6-42	1900	79.8	
		6-41	1950	80.0	
		6-40	2000	80.0	
BK-DAL080-BXXXXADR, BK-DBL080-AXXXXADN, BK-DBL080-AXXXXADPR	0.47	6-42	1000-2000	80.0	50