

CERTIFICATE

No. U6 089086 0472 Rev. 00

Holder of Certificate: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:




Product: **Electronic controlgear for LED modules
(Dimmable Constant Current LED Driver)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142245000401

Date, 2024-06-07



(Taylor Yao)

CERTIFICATE

No. U6 089086 0472 Rev. 00

Model(s): BK-DML022-B0600ADP; BK-DML022-B0600ADN;
BK-DML022-BxxxxADP; BK-DML022-BxxxxADN;
BK-DML040-B1100ADP; BK-DML040-B1100ADN;
BK-DML040-BxxxxADP; BK-DML040-BxxxxADN;
BK-DML060-B1650ADP; BK-DML060-B1650ADN;
BK-DML060-BxxxxADP; BK-DML060-BxxxxADN;
BK-DML080-B2200ADP; BK-DML080-B2200ADN;
BK-DML080-BxxxxADP; BK-DML080-BxxxxADN;
BK-DML150-B4000ADP; BK-DML150-B4000ADN;
BK-DML150-BxxxxADP; BK-DML150-BxxxxADN
(‘xxxx’=0100-3990 indicates rated output current
(I_{rated}) 100-3990mA, in steps of 10mA)

Brand Name: BOKE



Parameters:

Rated Input Voltage: 200-240V AC/DC
Rated Frequency: 0/50/60Hz
Rated Input Current: See below table for details
Rated Output: See below table for details
Protection against Electric Shock: Class I; SELV
Degree of Protection: IP65/IP67
Method of Installation: Independent
Type of Output: Constant current type
ta: 60°C
tc: 90°C

Tested according to: EN 61347-2-13:2014/A1:2017
EN 61347-1:2015/A1:2021
EN IEC 62384:2020

Production Facility(ies): 089086

CERTIFICATE

No. U6 089086 0472 Rev. 00

Model	Rated Input Current (A) Max.	Output Voltage (VDC)	I _{rated} (mA)	P _{rated} (W) Max.	U _{out} (VDC)
BK-DML022-B0600ADP, BK-DML022-B0600ADN	0.14	12-42	100-600	22.8	50
BK-DML022-BxxxxADP, BK-DML022-BxxxxADN	0.14	12-38	550-590	22.42	50
		12-40	510-550	22.0	
		12-42	100-500	21.0	
BK-DML040-B1100ADP, BK-DML040-B1100ADN	0.25	12-42	400-1100	42.0	50
BK-DML040-BxxxxADP, BK-DML040-BxxxxADN	0.25	12-38	1060-1090	41.42	50
		12-40	1010-1050	42.0	
		12-42	400-1000	42.0	
BK-DML060-B1650ADP, BK-DML060-B1650ADN	0.37	12-42	600-1650	63.0	50
BK-DML060-BxxxxADP, BK-DML060-BxxxxADN	0.37	12-38	1560-1640	62.32	50
		12-40	1510-1550	62.0	
		12-42	600-1500	63.0	
BK-DML080-B2200ADP, BK-DML080-B2200ADN	0.55	12-42	800-2200	84.0	50
BK-DML080-BxxxxADP, BK-DML080-BxxxxADN	0.55	12-38	2110-2190	83.22	50
		12-40	2010-2100	84.0	
		12-42	800-2000	84.0	
BK-DML150-B4000ADP, BK-DML150-B4000ADN	0.86	24-42	1500-4000	152.0	50
BK-DML150-BxxxxADP, BK-DML150-BxxxxADN	0.86	24-38	3810-3990	151.62	50
		24-40	3610-3800	152.0	
		24-42	1500-3600	151.2	