

CERTIFICATE

No. U6 089086 0111 Rev. 03

Holder of Certificate: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:




Product: **Power supplies**
(Constant Current LED Driver)

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142215000904

Date, 2023-08-14



(Taylor Yao)

CERTIFICATE

No. U6 089086 0111 Rev. 03

Model(s):

BK-DEL030-0800Ad; BK-DEL030-0800AD;
 BK-DEL042-1100Ad; BK-DEL042-1100AD;
 BK-DEL042-0800Bd; BK-DEL042-0800BD;
 BK-DEL060-2000Ad; BK-DEL060-2000AD;
 BK-DEL030-B0800Ad; BK-DEL030-B0800AD;
 BK-DEL030-B0800ADL; BK-DEL042-B1100Ad;
 BK-DEL042-B1100AD; BK-DEL042-B1100ADL;
 BK-DEL042-B0800Bd; BK-DEL042-B0800BD;
 BK-DEL042-B0800BDL; BK-DEL060-B2000Ad;
 BK-DEL060-B2000AD; BK-DEL060-B2000ADL;
 BK-DEL010-0350Ad; BK-DEL010-0350AD;
 BK-DEL022-0600Ad; BK-DEL022-0600AD;
 BK-DEL028-0750Ad; BK-DEL028-0750AD;
 BK-DEL010-B0350Ad; BK-DEL010-B0350AD;
 BK-DUL010-B0350ADP; BK-DUL010-B0350ADF;
 BK-DUL010-B0350AM; BK-DUL010-B0350AP;
 BK-DEL010-B0350ADL; BK-DUL010-B0350ADPL;
 BK-DUL010-B0350ADFL; BK-DUL010-B0350AML;
 BK-DUL010-B0350APL; BK-DEL022-B0600Ad;
 BK-DEL022-B0600AD; BK-DUL022-B0600ADP;
 BK-DUL022-B0600ADF; BK-DUL022-B0600AM;
 BK-DUL022-B0600AP; BK-DEL022-B0600ADL;
 BK-DUL022-B0600ADPL; BK-DUL022-B0600ADFL;
 BK-DUL022-B0600AML; BK-DUL022-B0600APL;
 BK-DEL028-B0750Ad; BK-DEL028-B0750AD;
 BK-DEL028-B0750AD; BK-DUL028-B0750ADP;
 BK-DUL028-B0750ADF; BK-DUL028-B0750AM;
 BK-DUL028-B0750AP; BK-DEL028-B0750ADL;
 BK-DUL028-B0750ADPL; BK-DUL028-B0750ADFL;
 BK-DUL028-B0750AML; BK-DUL028-B0750APL;
 BK-DUL030-B0800ADP; BK-DUL030-B0800ADF;
 BK-DUL030-B0800AM; BK-DUL030-B0800AP;
 BK-DUL030-B0800ADPL; BK-DUL030-B0800ADFL;
 BK-DUL030-B0800AML; BK-DUL030-B0800APL;
 BK-DEL040-B1050Ad; BK-DEL040-B1050AD;
 BK-DUL040-B1050ADF; BK-DUL040-B1050ADP;
 BK-DUL040-B1050AM; BK-DUL040-B1050AP;
 BK-DUL042-B1100ADP; BK-DUL042-B1100ADF;
 BK-DUL042-B1100AM; BK-DUL042-B1100AP;
 BK-DUL042-B1100ADPL; BK-DUL042-B1100ADFL;
 BK-DUL042-B1100AML; BK-DUL042-B1100APL;
 BK-DUL060-B2000ADP; BK-DUL060-B2000ADF;

CERTIFICATE

No. U6 089086 0111 Rev. 03

BK-DUL060-B2000AM; BK-DUL060-B2000AP;
 BK-DUL060-B2000ADPL; BK-DUL060-B2000ADFL;
 BK-DUL060-B2000AML; BK-DUL060-B2000APL;
 BK-DCL010-A0350AD; BK-DCL010-A0700AD;
 BK-DCL010-B0350AD; BK-DCL010-B0700AD

Brand Name: BOKE



Parameters:

Rated Input Voltage: 200-240V AC/DC
 Rated Frequency: 0/50/60Hz
 Rated Input Current: See below table for details
 Rated Output: See below table for details
 Protection against Electric Shock: Class II; SELV
 Degree of Protection: IP20
 Method of Installation: Independent
 Type of Output: Constant current type
 ta: See below table for details
 tc: 90°C

Tested according to: EN 61347-1:2015/A1:2021
 EN 61347-2-13:2014/A1:2017
 EN IEC 62384:2020

Production Facility(ies): 089086

CERTIFICATE

No. U6 089086 0111 Rev. 03

Model No.	Rated Input Current (A) Max.	Output Voltage (VDC)	I _{rated} (mA)	P _{rated} (W)	U _{out} (VDC)	ta (°C)
BK-DEL030-0800Ad BK-DEL030-0800AD	0.18	6-42	250	10.5	50	45
		6-42	275	11.55		
		6-42	300	12.6		
		6-42	325	13.65		
		6-42	350	14.7		
		6-42	375	15.75		
		6-42	400	16.8		
		6-42	425	17.85		
		6-42	450	18.9		
		6-42	500	21		
		6-42	550	23.1		
		6-42	600	25.2		
		6-42	650	27.3		
		6-40	750	30		
6-38	800	30.4				
BK-DEL042-1100Ad BK-DEL042-1100AD	0.25	6-42	450	18.9	50	45
		6-42	475	19.95		
		6-42	500	21		
		6-42	525	22.05		
		6-42	550	23.1		
		6-42	600	25.2		
		6-42	650	27.3		
		6-42	700	29.4		
		6-42	750	31.5		
		6-42	800	33.6		
		6-42	850	35.7		
		6-42	900	37.8		
		6-42	950	39.9		
		6-40	1050	42		
6-38	1100	41.8				
BK-DEL042-0800Bd BK-DEL042-0800BD	0.25	6-84	250	21	100	45
		6-84	275	23.1		
		6-84	300	25.2		
		6-84	325	27.3		
		6-84	350	29.4		
		6-84	375	31.5		
		6-84	400	33.6		
		6-84	425	35.7		
		6-84	450	37.8		
		6-84	500	42		
		6-76	550	41.8		
		6-70	600	42		
		6-64	650	41.6		
		6-60	700	42		
6-54	750	42				
6-52	800	41.6				

CERTIFICATE

No. U6 089086 0111 Rev. 03

ZERTIFIKAT ◆ CERTIFICATE ◆ 認 證 證 書 ◆ CERTIFICADO ◆ СЕРТИФИКАТ ◆ CERTIFICAT

BK-DEL060-2000Ad BK-DEL060-2000AD	0.36	6-42	800	33.6	50	45
		6-42	900	37.8		
		6-42	1000	42		
		6-42	1050	44.1		
		6-42	1100	46.2		
		6-42	1150	48.3		
		6-42	1200	50.4		
		6-42	1250	52.5		
		6-42	1300	54.6		
		6-42	1400	58.8		
		6-40	1500	60		
		6-38	1600	60.8		
		6-36	1700	61.2		
		6-34	1800	61.2		
		BK-DEL030-B0800Ad BK-DEL030-B0800AD BK-DEL030-B0800ADL	0.18	6-42		
6-42	275			11.55		
6-42	300			12.6		
6-42	325			13.65		
6-42	350			14.7		
6-42	375			15.75		
6-42	400			16.8		
6-42	425			17.85		
6-42	450			18.9		
6-42	500			21		
6-42	550			23.1		
6-42	600			25.2		
6-42	650			27.3		
6-42	700			29.4		
6-40	750			30		
BK-DEL042-B1100Ad BK-DEL042-B1100AD BK-DEL042-B1100ADL	0.25	6-42	450	18.9	50	45
		6-42	475	19.95		
		6-42	500	21		
		6-42	525	22.05		
		6-42	550	23.1		
		6-42	600	25.2		
		6-42	650	27.3		
		6-42	700	29.4		
		6-42	750	31.5		
		6-42	800	33.6		
		6-42	850	35.7		
		6-42	900	37.8		
		6-42	950	39.9		
		6-42	1000	42		
		6-40	1050	42		
6-38	1100	41.8				

CERTIFICATE

No. U6 089086 0111 Rev. 03

BK-DEL042-B0800Bd BK-DEL042-B0800BD BK-DEL042-B0800BDL	0.22	6-48	250	12.0	60	45
		6-48	275	13.2		
		6-48	300	14.4		
		6-48	325	15.6		
		6-48	350	16.8		
		6-48	375	18.0		
		6-48	400	19.2		
		6-48	425	20.4		
		6-48	450	21.6		
		6-48	500	24.0		
		6-48	550	26.4		
		6-48	600	28.8		
		6-48	650	31.2		
		6-48	700	33.6		
BK-DEL060-B2000Ad BK-DEL060-B2000AD BK-DEL060-B2000ADL	0.36	6-48	750	36.0	50	45
		6-48	800	38.4		
		6-42	800	33.6		
		6-42	900	37.8		
		6-42	1000	42		
		6-42	1050	44.1		
		6-42	1100	46.2		
		6-42	1150	48.3		
		6-42	1200	50.4		
		6-42	1250	52.5		
		6-42	1300	54.6		
		6-42	1400	58.8		
		6-40	1500	60		
		6-38	1600	60.8		
BK-DEL010-0350Ad BK-DEL010-0350AD	0.07	6-36	1700	61.2	50	60
		6-34	1800	61.2		
		6-32	1900	60.8		
		6-30	2000	60		
		6-42	100	4.2		
		6-42	125	5.25		
		6-42	150	6.3		
		6-42	175	7.35		
		6-42	200	8.4		
		6-42	225	9.45		
BK-DEL022-0600Ad BK-DEL022-0600AD	0.14	6-42	250	10.5	50	50
		6-42	275	11.55		
		6-42	300	12.6		
		6-42	350	14.7		
		6-42	400	16.8		
		6-42	450	18.9		
		6-42	500	21.0		
		6-42	550	23.1		
		6-38	600	22.8		

CERTIFICATE

No. U6 089086 0111 Rev. 03

BK-DEL028-0750Ad BK-DEL028-0750AD	0.18	6-42	300	12.6	50	45
		6-42	350	14.7		
		6-42	400	16.8		
		6-42	450	18.9		
		6-42	500	21.0		
		6-42	550	23.1		
		6-42	600	25.2		
		6-42	650	27.3		
		6-40	700	28.0		
		6-38	750	28.5		
BK-DEL010-B0350Ad BK-DEL010-B0350AD BK-DEL010-B0350ADL BK-DUL010-B0350ADP BK-DUL010-B0350ADPL BK-DUL010-B0350ADF BK-DUL010-B0350ADFL BK-DUL010-B0350AM BK-DUL010-B0350AML BK-DUL010-B0350AP BK-DUL010-B0350APL	0.07	6-42	100	4.2	50	60
		6-42	125	5.25		
		6-42	150	6.3		
		6-42	175	7.35		
		6-42	200	8.4		
		6-42	225	9.45		
		6-42	250	10.5		
		6-40	275	11.0		
		6-36	300	10.8		
		6-30	350	10.5		
		BK-DEL022-B0600Ad BK-DEL022-B0600AD BK-DEL022-B0600ADL BK-DUL022-B0600ADP BK-DUL022-B0600ADPL BK-DUL022-B0600ADF BK-DUL022-B0600ADFL BK-DEL022-B0600AM BK-DEL022-B0600AML BK-DEL022-B0600AP BK-DEL022-B0600APL	0.14	6-42		
6-42	250			10.5		
6-42	275			11.55		
6-42	300			12.6		
6-42	350			14.7		
6-42	400			16.8		
6-42	450			18.9		
6-42	500			21.0		
6-42	550			23.1		
6-38	600			22.8		
BK-DEL028-B0750Ad BK-DEL028-B0750AD BK-DEL028-B0750ADL BK-DUL028-B0750ADP BK-DUL028-B0750ADPL BK-DUL028-B0750ADF BK-DUL028-B0750ADFL BK-DUL028-B0750AM BK-DUL028-B0750AML BK-DUL028-B0750AP BK-DUL028-B0750APL	0.18			6-42	300	12.6
		6-42	350	14.7		
		6-42	400	16.8		
		6-42	450	18.9		
		6-42	500	21.0		
		6-42	550	23.1		
		6-42	600	25.2		
		6-42	650	27.3		
		6-40	700	28.0		
		6-38	750	28.5		

CERTIFICATE

No. U6 089086 0111 Rev. 03

BK-DUL030-B0800ADP BK-DUL030-B0800ADPL BK-DUL030-B0800ADF BK-DUL030-B0800ADFL BK-DUL030-B0800AM BK-DUL030-B0800AML BK-DUL030-B0800AP BK-DUL030-B0800APL	0.18	6-42	250	10.5	50	45
		6-42	275	11.55		
		6-42	300	12.6		
		6-42	325	13.65		
		6-42	350	14.7		
		6-42	375	15.75		
		6-42	400	16.8		
		6-42	425	17.85		
		6-42	450	18.9		
		6-42	500	21.0		
		6-42	550	23.1		
		6-42	600	25.2		
		6-42	650	27.3		
		6-42	700	29.4		
		6-40	750	30.0		
BK-DEL040-B1050Ad BK-DEL040-B1050AD BK-DUL040-B1050ADF BK-DUL040-B1050ADP BK-DUL040-B1050AM BK-DUL040-B1050AP	0.24	6-38	800	30.4	50	45
		6-42	600	25.2		
		6-42	650	27.3		
		6-42	700	29.4		
		6-42	750	31.5		
		6-42	800	33.6		
		6-42	850	35.7		
		6-42	900	37.8		
		6-42	950	39.9		
		6-40	1000	40.0		
6-38	1050	39.9				
BK-DUL042-B1100ADP BK-DUL042-B1100ADPL BK-DUL042-B1100ADF BK-DUL042-B1100ADFL BK-DUL042-B1100AM BK-DUL042-B1100AML BK-DUL042-B1100AP BK-DUL042-B1100APL	0.25	6-42	450	18.9	50	45
		6-42	475	19.95		
		6-42	500	21.0		
		6-42	525	22.05		
		6-42	550	23.1		
		6-42	600	25.2		
		6-42	650	27.3		
		6-42	700	29.4		
		6-42	750	31.5		
		6-42	800	33.6		
		6-42	850	35.7		
		6-42	900	37.8		
		6-42	950	39.9		
		6-42	1000	42.0		
		6-40	1050	42.0		
6-38	1100	41.8				

CERTIFICATE

No. U6 089086 0111 Rev. 03

BK-DUL060-B2000ADP BK-DUL060-B2000ADPL BK-DUL060-B2000ADF BK-DUL060-B2000ADFL BK-DUL060-B2000AM BK-DUL060-B2000AML BK-DUL060-B2000AP BK-DUL060-B2000APL	0.36	6-42	800	33.6	50	45
		6-42	900	37.8		
		6-42	1000	42.0		
		6-42	1050	44.1		
		6-42	1100	46.2		
		6-42	1150	48.3		
		6-42	1200	50.4		
		6-42	1250	52.5		
		6-42	1300	54.6		
		6-42	1400	58.8		
		6-40	1500	60.0		
		6-38	1600	60.8		
		6-36	1700	61.2		
		6-34	1800	61.2		
		6-32	1900	60.8		
6-30	2000	60.0				
BK-DCL010-A0350AD	0.066	12-42	100	4.2	50	60
		12-42	150	6.3		
		12-42	175	7.35		
		12-42	200	8.4		
		12-42	250	10.5		
		12-39	275	10.73		
		12-36	300	10.8		
		12-30	350	10.5		
BK-DCL010-A0700AD	0.066	6-27	350	9.45	35	60
		6-27	400	10.8		
		6-24	450	10.8		
		6-21	500	10.5		
		6-18	550	9.9		
		6-18	600	10.8		
		6-15	650	9.75		
		6-15	700	10.5		
BK-DCL010-B0350AD	0.066	6-42	100	4.2	50	60
		6-42	150	6.3		
		6-42	175	7.35		
		6-42	200	8.4		
		6-42	250	10.5		
		6-39	275	10.73		
		6-36	300	10.8		
		6-30	350	10.5		
BK-DCL010-B0700AD	0.066	3-27	350	9.45	35	60
		3-27	400	10.8		
		3-24	450	10.8		
		3-21	500	10.5		
		3-18	550	9.9		
		3-18	600	10.8		
		3-15	650	9.75		
		3-15	700	10.5		