

CERTIFICATE

No. U6 089086 0159 Rev. 00

Holder of Certificate: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:




Product: **Power supplies**
(Dimmable Tunable White LED Driver)

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142215026601

Date, 2022-03-21



(Taylor Yao)

CERTIFICATE

No. U6 089086 0159 Rev. 00

Model(s): BK-DWL010-0350AD; BK-DWL022-0450AD;
BK-DWL022-0600AD; BK-DWL030-0800AD;
BK-DWL042-1050AD; BK-DWL060-1500AD;
BK-DWL060-2000AD

Brand Name: BOKE



Parameters:

Rated Input Voltage: 200-240V AC/DC

Rated Frequency: 0/50/60Hz

Rated Input Current: See below table for details

Rated Output: See below table for details

Protection against Electric Shock: Class II (with endcap); SELV

Degree of Protection: IP20 (with endcap)

Method of Installation: Independent (with endcap);

Built-in (without endcap)

Type of Output: Constant current type

ta: See below table for details

tc: See below table for details

Tested according to: EN 61347-1:2015/A1:2021
EN 61347-2-13:2014/A1:2017
EN IEC 62384:2020

Production Facility(ies): 089086

CERTIFICATE

No. U6 089086 0159 Rev. 00

Model	Rated Input Current (A) Max.	Output Voltage (VDC)	I _{rated} (mA)	U _{out} (VDC)	P _{rated} (W)	ta/tc Value (°C)
BK-DWL010-0350AD	0.07	12-54	100	60	5.4	60/90
		12-54	125		6.75	
		12-54	150		8.1	
		12-54	175		9.45	
		12-54	200		10.8	
		12-48	225		10.8	
		12-44	250		11.0	
		12-40	275		11.0	
		12-36	300		10.8	
		12-30	350		10.5	
BK-DWL022-0450AD	0.14	12-54	150	60	8.10	60/90
		12-54	175		9.45	
		12-54	200		10.8	
		12-54	225		12.15	
		12-54	250		13.5	
		12-54	275		14.85	
		12-54	300		16.2	
		12-54	350		18.9	
		12-54	400		21.6	
		12-50	450		22.5	
BK-DWL022-0600AD	0.14	12-54	225	60	12.15	50/90
		12-54	250		13.5	
		12-54	275		14.85	
		12-54	300		16.2	
		12-54	350		18.9	
		12-54	400		21.6	
		12-50	450		22.5	
		12-46	500		23.0	
		12-42	550		23.1	
		12-38	600		22.8	
BK-DWL030-0800AD	0.18	12-54	350	60	18.9	50/90
		12-54	400		21.6	
		12-54	450		24.3	
		12-54	500		27.0	
		12-54	550		29.7	
		12-54	600		32.4	
		12-50	650		32.5	
		12-46	700		32.2	
		12-42	750		31.5	
		12-38	800		30.4	

CERTIFICATE

No. U6 089086 0159 Rev. 00

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFIKAT ◆ CERTIFICAT

BK-DWL042-1050AD	0.25	12-42	600	50	25.2	50/85
		12-42	650		27.3	
		12-42	700		29.4	
		12-42	750		31.5	
		12-42	800		33.6	
		12-42	850		35.7	
		12-42	900		37.8	
		12-42	950		39.9	
		12-42	1000		42.0	
		12-40	1050		42.0	
BK-DWL060-1500AD	0.36	12-42	1050	50	44.1	50/85
		12-42	1100		46.2	
		12-42	1150		48.3	
		12-42	1200		50.4	
		12-42	1250		52.5	
		12-42	1300		54.6	
		12-42	1350		56.7	
		12-42	1400		58.8	
		12-42	1450		60.9	
		12-42	1500		63.0	
BK-DWL060-2000AD	0.36	12-42	1550	50	65.1	50/85
		12-40	1600		64.0	
		12-40	1650		66.0	
		12-38	1700		64.6	
		12-36	1750		63.0	
		12-35	1800		63.0	
		12-34	1850		62.9	
		12-33	1900		62.7	
		12-32	1950		62.4	
		12-31	2000		62.0	45/85