

CERTIFICATE

No. U6 089086 0127 Rev. 01

Holder of Certificate: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:




Product: **Power supplies**
(Dimmable Constant Current LED Driver)

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142215012402

Date, 2022-07-14



(Taylor Yao)

CERTIFICATE

No. U6 089086 0127 Rev. 01

Model(s): BK-KUL050-1300Am; BK-KUL040-1050Am;
BK-KUL030-0800Am; BK-KUL060-1650Am

Brand Name: BOKE



Parameters:

Rated Input Voltage: 200-240V AC/DC

Rated Frequency: 0/50/60Hz

Rated Input Current: See below table for details

Rated Output: See below table for details

Protection against Electric Shock: Class II; SELV

Degree of Protection: IP20

Method of Installation: Independent

Type of Output: Constant current type

ta: 45°C

tc: See below table for details

Tested according to: EN 61347-1:2015/A1:2021
EN 61347-2-13:2014/A1:2017
EN IEC 62384:2020

Production Facility(ies): 089086

CERTIFICATE

No. U6 089086 0127 Rev. 01

Model	Rated Input Current (A) Max.	Output Voltage (VDC)	I _{rated} (mA)	U _{out} (VDC)	P _{rated} (W)	tc (°C)
BK-KUL050-1300Am	0.29	24-38	1300	50	49.4	80
		24-40	1250		50.0	
		24-42	1200		50.4	
		24-42	1150		48.3	
		24-42	1100		46.2	
		24-42	1050		44.1	
		24-42	1000		42.0	
		24-42	950		39.9	
		24-42	900		37.8	
		24-42	850		35.7	
BK-KUL040-1050Am	0.24	24-38	1050	50	39.9	90
		24-40	1000		40.0	
		24-42	950		39.9	
		24-42	900		37.8	
		24-42	850		35.7	
		24-42	800		33.6	
		24-42	750		31.5	
		24-42	700		29.4	
		24-42	650		27.3	
		24-42	600		25.2	
BK-KUL030-0800Am	0.21	24-38	800	50	30.4	80
		24-40	750		30.0	
		24-42	700		29.4	
		24-42	650		27.3	
		24-42	600		25.2	
		24-42	550		23.1	
		24-42	500		21.0	
		24-42	450		18.9	
		24-42	400		16.8	
		24-42	350		14.7	



Product Service

CERTIFICATE

No. U6 089086 0127 Rev. 01

BK-KUL060-1650Am	0.37	24-42	1200	50	50.4	90
		24-42	1250		52.5	
		24-42	1300		54.6	
		24-42	1350		56.7	
		24-42	1400		58.8	
		24-42	1450		60.9	
		24-40	1500		60.0	
		24-40	1550		62.0	
		24-38	1600		60.8	
		24-38	1650		62.7	