

CERTIFICATE

No. U6 089086 0245 Rev. 00

Holder of Certificate: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:




Product: **Power supplies**
(Dimmable Constant Voltage LED Driver)

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142215026001

Date, 2022-09-28



(Taylor Yao)

CERTIFICATE

No. U6 089086 0245 Rev. 00

Model(s): BK-MGV036-24V0m; BK-MGV036-24V0M;
BK-MGV036-48V0m; BK-MGV036-48V0M;
BK-MGV060-24V0m; BK-MGV060-24V0M;
BK-MGV060-48V0m; BK-MGV060-48V0M;
BK-MGV100-24V0m; BK-MGV100-24V0M;
BK-MGV100-48V0m; BK-MGV100-48V0M;
BK-MGV150-24V0m; BK-MGV150-24V0M;
BK-MGV150-48V0m; BK-MGV150-48V0M;
BK-MGV200-24V0m; BK-MGV200-24V0M;
BK-MGV200-48V0m; BK-MGV200-48V0M

Brand Name: BOKE



Parameters:

Rated Input Voltage: 200-240VAC

Rated Frequency: 50/60Hz

Rated Input Current: See below table for details

Rated Output: See below table for details

Protection against Electric Shock: Class I (with endcap); SELV

Degree of Protection: IP20 (with endcap)

Method of Installation: Independent (with endcap); Built-in (without endcap)

Type of Output: Constant voltage type

ta: 60°C

tc: 90°C



CERTIFICATE

No. U6 089086 0245 Rev. 00

Model	Rated Input Current (A) Max.	U _{rated} (VDC)	Output Current (A)	P _{rated} (W) Max.
BK-MGV036-24V0m; BK-MGV036-24V0M	0.25	24	1.5	36.0
BK-MGV036-48V0m; BK-MGV036-48V0M	0.25	48	0.75	36.0
BK-MGV060-24V0m; BK-MGV060-24V0M	0.35	24	2.5	60.0
BK-MGV060-48V0m; BK-MGV060-48V0M	0.35	48	1.2	57.6
BK-MGV100-24V0m; BK-MGV100-24V0M	0.65	24	4.2	100.0
BK-MGV100-48V0m; BK-MGV100-48V0M	0.65	48	2.09	100.0
BK-MGV150-24V0m; BK-MGV150-24V0M	1.0	24	6.25	150.0
BK-MGV150-48V0m; BK-MGV150-48V0M	1.0	48	3.12	150.0
BK-MGV200-24V0m; BK-MGV200-24V0M	1.1	24	8.3	199.2
BK-MGV200-48V0m; BK-MGV200-48V0M	1.1	48	4.15	199.2

**Tested
according to:**

EN 61347-1:2015/A1:2021
EN 61347-2-13:2014/A1:2017
EN IEC 62384:2020

**Production
Facility(ies):**

089086