

CERTIFICATE

No. U6 089086 0462 Rev. 00

Holder of Certificate: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:




Product: **Electronic controlgear for LED modules
(Constant Voltage LED Driver)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the Testing, Certification, Validation and Verification Regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142235026601

Date, 2024-05-17



(Taylor Yao)

CERTIFICATE

No. U6 089086 0462 Rev. 00

Model(s):

BK-PGV020-12V0; BK-PGV020-24V0; BK-PGV020-48V0;
BK-PGV024-12V0; BK-PGV024-24V0; BK-PGV024-48V0;
BK-PGV030-12V0; BK-PGV030-24V0; BK-PGV030-48V0;
BK-PGV036-12V0; BK-PGV036-24V0; BK-PGV036-48V0;
BK-PGV048-12V0; BK-PGV048-24V0; BK-PGV048-48V0;
BK-PGV060-12V0; BK-PGV060-24V0; BK-PGV060-48V0;
BK-PGV072-12V0; BK-PGV072-24V0; BK-PGV072-48V0;
BK-PGV100-12V0; BK-PGV100-24V0; BK-PGV100-48V0

Brand Name:

BOKE

**Parameters:**

Rated Input Voltage: 200-240V AC/DC

Rated Frequency: 0/50/60Hz

Rated Input Current: See below table for details

Rated Output: See below table for details

Protection against Electric Shock: Class II; SELV

Degree of Protection: IP20

Method of Installation: Independent

Type of Output: Constant voltage type

ta: 45°C

tc: See below table for details

Tested**according to:**

EN 61347-2-13:2014/A1:2017

EN 61347-1:2015/A1:2021

EN IEC 62384:2020

Production**Facility(ies):**

089086

CERTIFICATE

No. U6 089086 0462 Rev. 00

Model	Rated Input Current (A) Max.	U _{rated} (VDC)	Output Current (A)	P _{rated} (W) Max.	tc (°C)
BK-PGV020-12V0	0.2	12	1.67	20	85
BK-PGV020-24V0	0.2	24	0.83	20	85
BK-PGV020-48V0	0.2	48	0.42	20	85
BK-PGV024-12V0	0.2	12	2.0	24	85
BK-PGV024-24V0	0.2	24	1.0	24	85
BK-PGV024-48V0	0.2	48	0.5	24	85
BK-PGV030-12V0	0.25	12	2.5	30	85
BK-PGV030-24V0	0.25	24	1.25	30	85
BK-PGV030-48V0	0.25	48	0.63	30	85
BK-PGV036-12V0	0.25	12	3.0	36	85
BK-PGV036-24V0	0.25	24	1.5	36	85
BK-PGV036-48V0	0.25	48	0.75	36	85
BK-PGV048-12V0	0.4	12	4.0	48	85
BK-PGV048-24V0	0.4	24	2.0	48	85
BK-PGV048-48V0	0.4	48	1.0	48	85
BK-PGV060-12V0	0.5	12	5.0	60	85
BK-PGV060-24V0	0.5	24	2.5	60	85
BK-PGV060-48V0	0.5	48	1.25	60	85
BK-PGV072-12V0	0.65	12	6.0	72	90
BK-PGV072-24V0	0.65	24	3.0	72	90
BK-PGV072-48V0	0.65	48	1.50	72	90
BK-PGV100-12V0	0.78	12	8.3	100	90
BK-PGV100-24V0	0.78	24	4.2	100	90
BK-PGV100-48V0	0.78	48	2.1	100	90