

# CERTIFICATE

No. U6 089086 0344 Rev. 00

**Holder of Certificate:** **BOKE Drivers Co., Ltd.**  
2nd and 3rd Floor, No.51, Xihuan 5th Road  
South District  
528455 Zhongshan City, Guangdong  
PEOPLE'S REPUBLIC OF CHINA

**Certification Mark:**




**Product:** **Power supplies  
(Constant Current LED Driver)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: [www.tuvsud.com/ps-cert](http://www.tuvsud.com/ps-cert)

**Test report no.:** 64142235001501

**Date,** 2023-04-19



( Taylor Yao )

# CERTIFICATE

No. U6 089086 0344 Rev. 00

**Model(s):** BK-PPL018-BxxxxA, BK-PPL022-BxxxxA,  
BK-PPL040-BxxxxA, BK-PPL050-BxxxxA,  
BK-PPL060-BxxxxA  
(‘xxxx’=0150-1650 indicates rated output current  
(I<sub>rated</sub>) 150-1650mA, in steps of 10mA)

**Brand Name:** BOKE



## Parameters:

Rated Input Voltage: 200-240V AC/DC  
Rated Frequency: 0/50/60Hz  
Rated Input Current: See below table for details  
Rated Output: See below table for details  
Protection against Electric Shock: Class II; SELV  
Degree of Protection: IP65  
Method of Installation: Independent  
Type of Output: Constant current type  
ta: 60°C  
tc: 90°C



Product Service

# CERTIFICATE

No. U6 089086 0344 Rev. 00

Model	Rated Input Current (A) Max.	Output Voltage (VDC)	I <sub>rated</sub> (mA)	P <sub>rated</sub> (W) Max.	U <sub>out</sub> (VDC)
BK-PPL018-BxxxxA	0.11	28-42	150-400	16.8	50
		28-40	410-450	18.0	
BK-PPL022-BxxxxA	0.14	28-42	150-500	21.0	50
		28-40	510-550	22.0	
		28-38	560-600	22.8	
BK-PPL040-BxxxxA	0.24	30-42	500-950	39.9	50
		30-40	960-1000	40.0	
BK-PPL050-BxxxxA	0.29	28-42	800-1200	50.4	50
		28-40	1210-1250	50.0	
BK-PPL060-BxxxxA	0.38	28-42	1000-1500	63.0	50
		28-40	1510-1550	62.0	
		28-38	1560-1650	62.7	

**Tested according to:**

EN 61347-1:2015/A1:2021  
EN 61347-2-13:2014/A1:2017  
EN IEC 62384:2020

**Production Facility(ies):**

089086

ZERTIFIKAT ◆ CERTIFICATE ◆ 認證證書 ◆ CERTIFICADO ◆ CERTIFIKAT ◆ CERTIFICATE