

CERTIFICATE

No. U6 089086 0190 Rev. 00

Holder of Certificate: **BOKE Drivers Co., Ltd.**
2nd and 3rd Floor, No.51, Xihuan 5th Road
South District
528455 Zhongshan City, Guangdong
PEOPLE'S REPUBLIC OF CHINA

Certification Mark:




Product: **Power supplies
(Constant Current LED Driver)**

The product was voluntarily tested according to the listed standards. The product can be marked with the certification mark shown above. It is not permitted to alter the certification mark in any way. In addition, the certificate holder must not transfer the certificate to third parties. All applicable requirements of the testing and certification regulations of TÜV SÜD Group have to be complied. For details see: www.tuvsud.com/ps-cert

Test report no.: 64142215024001

Date, 2022-05-23



(Taylor Yao)

CERTIFICATE

No. U6 089086 0190 Rev. 00

Model(s): BK-PQL009-BXXXXA; BK-PQL013-BXXXXA;
 BK-PQL018-BXXXXA; BK-PQL022-BXXXXA;
 BK-PQL018-CXXXXA; BK-PQL022-CXXXXA;
 BK-PQL040-BXXXXA; BK-PQL042-BXXXXA;
 BK-PQL050-BXXXXA; BK-PQL060-BXXXXA
 ('XXXX'=0150-1650 indicates rated output current
 (I_{rated}) 0.15- 1.65A, in steps of 0.01A)

Brand Name: BOKE



Parameters:

Rated Input Voltage: 200-240V AC/DC
 Rated Frequency: 0/50/60Hz
 Rated Input Current: See below table for details
 Rated Output: See below table for details
 Protection against Electric Shock: Class II; SELV
 Degree of Protection: IP20
 Method of Installation: Independent
 Type of Output: Constant current type
 ta: See below table for details
 tc: See below table for details

Tested according to: EN 61347-1:2015/A1:2021
 EN 61347-2-13:2014/A1:2017
 EN IEC 62384:2020

Production Facility(ies): 089086

CERTIFICATE

No. U6 089086 0190 Rev. 00

Model	Rated Input Current (A) Max.	Output Voltage (VDC)	I _{rated} (mA)	U _{out} (VDC)	P _{rated} (W) Max.	ta/tc (°C)
BK-PQL009-BXXXXA	0.07	28-42	150-250	50	10.5	60/85
BK-PQL013-BXXXXA	0.09	28-42	250-300	50	12.6	50/90
		28-40	310-350		14.0	
BK-PQL018-BXXXXA	0.11	28-42	300-400	50	16.8	50/90
		28-40	410-450		18	
BK-PQL022-BXXXXA	0.14	28-42	400-500	50	21	50/90
		28-40	510-550		22	
		28-38	560-600		22.8	
BK-PQL018-CXXXXA	0.11	28-42	300-400	50	16.8	50/85
		28-40	410-450		18	
BK-PQL022-CXXXXA	0.14	28-42	400-500	50	21	50/90
		28-40	510-550		22	
		28-38	560-600		22.8	
BK-PQL040-BXXXXA	0.24	30-42	600-950	50	39.9	45/90
		30-40	960-1000		40	
BK-PQL042-BXXXXA	0.25	28-42	800-1000	50	42	45/90
		28-40	1010-1050		42	
		28-38	1060-1100		41.8	
BK-PQL050-BXXXXA	0.29	28-42	1000-1200	50	50.4	45/90
		28-40	1210-1250		50	
BK-PQL060-BXXXXA	0.38	28-42	1000-1500	50	63	45/90
		28-40	1510-1550		62	
		28-38	1560-1650		62.7	